



Laminating and
Finishing **SYSTEMS**

EXCELAM 1670 SWING

Large Format Graphic
Roll Laminator



 **skandacor**™ The proactive finish.™

1.888.820.9020
skandacor.com

EXCELAM 1670 SWING

Excelam-Swing Series has a built-in “Multi-Step” pressure control device to control the roller pressure for all kinds of paper. This machine is the best laminator for photocopy centers and graphic printing shops. Available in both 43” (1100 mm) and 65” (1670 mm) widths.

Finishing Applications in Wide Format Print Shops.



Max. 65.7” Wide



3 m/min



220-240 V, 20 A

Specifications

	EXCELAM 1670 SWING
Laminating Speed	3 m/min
Laminating Width	65.7”
Film Thickness	Up to 10 mil
Substrate weight	80 gsm~350 gsm
Max. Mounting Thickness	0.511”
Front Roller Diameter	3.15”
Rear Roller Diameter	2.36”
Warm Up Time	25 min
Heating System	Hot Roller Internal Infrared Heater
Dimensions	78.7” x 27.9” x 49.2”
Electrical	220-240 V, 20 A

Skandacor™ equipment works brilliantly with our lineup of **TRADEpro™** Wide Format UV Low-Melt and Cold laminate films.



TRADE
Laminate Films

Note: The information given within this spec sheet is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Skandacor™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The included data is purely for reader's consideration, investigation and verification.