



Systems and  
EQUIPMENT

# 460A PUR

High-Quality Perfect Binder



# 460A PUR

The **460A PUR** Perfect Binder is easy to use and gives excellent results for anyone looking for a short to medium length run solution for LayFlat binding. These machines are solidly built and include features that are normally standard on more expensive units.

**Finishing Applications** for Binding/Print Shops.



LayFlat  
Friendliness

## Specifications



Max. 18.1" Length



Up to 450 Books/Hour



220-240 V

|              | 460A PUR                                                                                                                                                                                                     |
|--------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Size         | Max. 18.1"Length / Max. 2.25" Thick                                                                                                                                                                          |
| Speed        | up to 450 Books/Hour                                                                                                                                                                                         |
| Warm Up Time | 20-30 min.                                                                                                                                                                                                   |
| Notching     | Double Layer (24 Blades)                                                                                                                                                                                     |
| Sheets       | Clamping Electric or Manual Push Button                                                                                                                                                                      |
| Cover        | Clamping Electric / Manual Insertion                                                                                                                                                                         |
| Gluing Unit  | Self-Adjusting PUR Side Glue / Hot Melt Glue Applied to Spine By Rotating Application Drum / Scraper Bar Ensure Smooth Uniform Thickness / High Quality Immediate Tack                                       |
| Features     | LCD Display / Enclosed Vacuum Dust Extraction / Automatic Clamping, Glue Application, Milling and Nipping / Sealed Tank System to Reduce Waste / Adjustable Automatic Nip Table Pressure for a Squarer Spine |
| Dimensions   | 62"L x 29"W x 51"H                                                                                                                                                                                           |
| Weight       | 575 lbs                                                                                                                                                                                                      |
| Electrical   | 220-240 V / 1 Phase / 20A                                                                                                                                                                                    |



**Skandacor™** is on mission to proactively pursue products, solutions, and services that will advance our clients brands and returns. Our **pro™** lineup of products and equipment creatively deliver the highest value through only the best in opportunity, quality, and performance.

**Note:** The information given within this spec sheet is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Skandacor™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The included data is purely for reader's consideration, investigation and verification.