

# TORNADO Die Selector

Rhin-O-Tuff Interchangeable Die Patterns for the Tornado AutoPunch EX Systems



| Part No.<br>/ Recommended<br>Sheet Size | Size and<br># of Holes    | Pitch /<br>Spacing         | Tool Pattern Style           | Margin |
|-----------------------------------------|---------------------------|----------------------------|------------------------------|--------|
| PUNCH EDGE CENTER LINE                  |                           |                            |                              |        |
| COIL                                    |                           |                            |                              |        |
| T0047<br>A4 and A5                      | 0.188"<br>47 HOLES        | 4:1 - 0.2475"<br>ROUND     | 1" PITCH SPACING EDGE MARGIN | 0.188" |
| T0047<br>LTR and 1/2 LTR                | 0.188"<br>48 HOLES        | 4:1 - 0.2475"<br>ROUND     |                              | 0.188" |
| T0247<br>A4 and A5                      | 0.188"x0.156<br>47 HOLES  | 4:1 - 0.2475"<br>OVAL      |                              | 0.188" |
| T0247<br>LTR and 1/2 LTR                | 0.188"x0.156<br>48 HOLES  | 4:1 - 0.2475"<br>OVAL      |                              | 0.188" |
| WIRE                                    |                           |                            |                              |        |
| T1136<br>All Standard Sizes             | 0.156"<br>36 HOLES        | 3:1 - 0.3333"<br>SQUARE    |                              | 0.179" |
| T2423<br>LTR and A4                     | 0.25"<br>23 HOLES         | 2:1 - 0.500"<br>SQUARE     |                              | 0.25"  |
| T2424<br>1/2 LTR and A5                 | 0.25"<br>24 HOLES         | 2:1 - 0.500"<br>SQUARE     |                              | 0.25"  |
| T1736<br>All Standard Sizes             | 0.171"<br>36 HOLES        | 3:1 - 0.3333"<br>ROUND     |                              | 0.168" |
| T2823<br>LTR and A4                     | 0.25"<br>23 HOLES         | 2:1 - 0.500"<br>ROUND      |                              | 0.25"  |
| T2824<br>1/2 LTR and A5                 | 0.25"<br>24 HOLES         | 2:1 - 0.500"<br>ROUND      |                              | 0.25"  |
| T1135<br>Non Standard Die               | 0.156"<br>35 HOLES        | 3:1 - 0.3333"<br>SQUARE    |                              | 0.179" |
| T1735<br>Non Standard Die               | 0.171"<br>35 HOLES        | 3:1 - 0.3333"<br>ROUND     |                              | 0.168" |
| COMB                                    |                           |                            |                              |        |
| T3321<br>All Standard Sizes             | 0.313"x0.125"<br>21 HOLES | 0.5625"<br>COMB            |                              | 0.2"   |
| T3320<br>Non Standard Die               | 0.313"x0.125"<br>20 HOLES | 0.5625"<br>COMB            |                              | 0.2"   |
| VELO                                    |                           |                            |                              |        |
| T4511<br>LTR / 1/2 LTR / A5             | 0.125"<br>11 HOLES        | 1"<br>VELO                 |                              | 0.125" |
| T4512<br>A4                             | 0.125"<br>12 HOLES        | 1"<br>VELO                 |                              | 0.125" |
| LOOSE LEAF                              |                           |                            |                              |        |
| T9609<br>LTR / 1/2 LTR                  | 0.313"<br>9 HOLES         | 3-5-7/2<br>HOLE MECHANICAL |                              | 0.313" |
| T9604<br>A4 / A5                        | 0.25"<br>4 HOLES          | ISO 838/888                |                              | 0.472" |