



Systems and
EQUIPMENT

PT 335A Plus Multi


Crease / Perf



PT 335A Plus Multi

The new **PT 335A Plus Multi** is a complete full-bleed finishing system to fit the digital marketplace. Equipped with interchangeable creasing/perfing dies, quickly switch over from perfing to creasing while preventing digital toner cracking. Strike perf capabilities means partial perfs are possible in both directions in a single pass for "T" or "box" perfs. The **PT 335A Plus Multi** built in colour touchscreen with job creator software provides quick and easy job changeover to maximize efficiency with less operator intervention.

Finishing Applications in Business Cards, Greeting Cards, Invitations, Brochures, Pamphlets, Catalogs, Posters, Book/CD Covers, Photographs, Tent Cards, and more.



Multi Perforating Capabilities

Specifications



Min. 5.5"W x 8.26"L
Max. 13"W x 35.4"L



Up to 8040
Sheets/Hour



110-130 V

	PT 335A Plus Multi
Size	Min. 5.5"W x 8.26"L / Max. 13"W x 35.4"L (40" Handfed)
Stock	NonCoated, Coated, Laminated / 150-400gsm
Speed	up to 8040 Sheets / Hour
Crease (Perf)	up to 32 Creases per Sheet
Interchangeable Dies	Linear Strike Perf up to four 12 or 24 Tpi / Crease Die (0.6mm, 1mm, 1.2mm, 1.4mm)
Features	LCD Display / 4" Pile Feeder / 64 Job Program Memory / 8 Depth settings controlled through touch screen/ Strike Perf Capabilities for "Box" and "T" Perfs / Image Shift Compensation on Both X and Y Axis / Image Shrink or Stretch Compensation for Both X and Y Axis / Partial Perfs in Both Directions in One Pass / Multi Accessory Output
Optional	Linear Score, Slit or Kiss-Cut Tools / Cross perforator / Additional Crease Widths / Outfeed Conveyor / Extension Table / Narrow Feeder (Min. 1.77" x 5.31")
Electrical	110-130 V / 15A



Skandacor™ is on mission to proactively pursue products, solutions, and services that will advance our clients brands and returns. Our **pro™** lineup of products and equipment creatively deliver the highest value through only the best in opportunity, quality, and performance.

Note: The information given within this spec sheet is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Skandacor™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The included data is purely for reader's consideration, investigation and verification.