

TORNADO AutoPunch EX

Auto Punch and Collate **Production System**





1.888.820.9020 skandacor.com

TORNADO AutoPunch EX

The Tornado AutoPunch EX by Rhin-O-Tuff® is an industry breakthrough system that uses BDT Print Media's advanced media handling technology to automatically fee, collage, punch and deliver offset book stacks ready for binding in a single platform. The system will save binding service providers an average of 40% in process efficiency, dramatically reducing overall costs. The Tornado AutoPunch EX handles the widest range of media in the industry, delivering unparalleled flexibility and enables concurrent binding operations. The system includes easy programmable job setup, monitoring and changeovers making it perfect for on-demand, short runs and high-volume production alike.

TORNADO AutoPunch EX

Finishing Applications

in Binding and Print Shops.



Specifications



Min. 5.5"W x 8.27"L Max. 12"W x 12.5"L



Sheets/Hour



TOTINADO Autor unen Ex
Punched Edge: 8.27"W to 12"L Unpunched Edge: 5.5" to 12.5" Index Tabs: up to 0.5" Tab Extension
60-312gsm (Uncoated Bond / Text / Offset / Coated / Plastic (Acetate, PVC Run From Interposer Bin Only) / Vinyl Covers and Tabs)
up to 2500 Sheets of 20lb Bond
up to 0.75" of Covers / Index Tabs / Insert Sheets
up to 10800 sph (Based on 20lb Bond)
up to 2100 Sheets of 20lb Bond
Letter and A4 Formats in 9 Binding Styles / Pins Pull Out for Various Paper Sizes
Plastic Comb: 19/21 Hole Coil: 4:1 Pitch Round or Oversized Oval Hole (0.2475") Double Loop Wire: 3:1 and 2:1 Pitch, Square and Round Hole Options VeloBind®: 11/12 Hole Loose-Leaf: 3-5-7 Hole, 2-Hole Medical (8.5" Side) / A4 2-4 Hole
7" Touch Screen Display / Tracks and Displays Number of Punch Cycles Per Die Set
59" L x 28" W x 59" H
770 lbs
115 v / 60Hz

Skandacor™ is proud to offer legendary equipment that works brilliantly in the binding finishing process and with our BINDpro[™] components.



Note: The information given within this spec sheet is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. SkandacorTM makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The included data is purely for reader's consideration, investigation and verification.

Skandacor™ The **pro**active finish.™

1.888.820.9020 skandacor.com