⊢ TRIUMPH 4810

SEMI-AUTOMATIC CUTTER \cdot electric blade drive \cdot spindle clamping system applies even pressure along entire cutting length \cdot spindle-guided back gauge with calibrated crank \cdot precision back gauge measuring scale on front table \cdot dual side guides on front and rear tables \cdot solid steel blade carrier \cdot stand with storage shelf \cdot **SAFETY FEATURES**: external blade depth adjustment \cdot two-hand operation \cdot transparent safety guards on front and rear tables \cdot automatic blade return from any position \cdot disc brake for instant blade stop \cdot safety lock with key and main switch

Dimensions (D x W x H): 38 $\frac{1}{4}$ x 29 $\frac{3}{4}$ x 53 $\frac{1}{2}$ inches, Shipping weight: 531 lbs.





3134 Industry Drive North Charleston, South Carolina 29418 800-223-2508, fax: 843-552-2974 www.mbmcorp.com





A calibrated hand crank ensures exact positioning of back gauge.

REAR SAFETY GUARD



The transparent rear safety guard gives a clear view of side guides and back gauge.

\mapsto TRIUMPH 4810	
Cutting width	18 7%"
Cutting height	3''
Narrow cut	1 ¼"
Cutting length behind blade	17 ¹¹ / ₁₆ ''
Table length in front of blade	13 5/8''
Motor	1.5 hp
Power supply	115 V, 60 Hz