

Laminating and Finishing **SYSTEMS**

LAMpro Cheetah S15 Photo

On-Demand, Professional, Compact Specialty Finishing Laminator & Photo Finisher with Flying Knife



Skandacor The proactive finish."

1.888.820.9020 skandacor.com

LAMpro Cheetah S15 Photo

LAMpro Cheetah S15 Photo

1.0 mil - 2.0 mil

14.25"

The Cheetah Photo allows digital printers to replace the traditional silver halide process with simple embossed lamination. This chemical-free process works by combining special laminate film technology with a high-quality digital print to create photos that retain the look, feel, and weight of traditional Silver Halide photos. But unlike the traditional process, the Cheetah Photo is more environmentally friendly — it uses no harmful chemicals and can lower costs by up to 40%.

Finishing Applications in Digital Print Shops, Photo Studios





Specifications

Film Thickness

Max Roll Diameter

Min. 7" x 8.25" Max. 15" x 48"*







6-15R

5-20R



Core Size	3"
Sheet Size*	Min: 7" x 8.25", Max: 15" x 22" Optional Table extension accepts up to 48"L sheet
Paper Weight*	Min: 120 gsm paper stock, Max: 400gsm paper stock (*depending on application)
Speed	Simplex lamination: 39 ft/min (1560 12x18 shts/hr) SLEEKpro: 16 ft/min (640 12x18 shts/hr) (depending on application) PHOTOpro Emboss Lamination: 20 ft/min (800 12 x 18 shts/hr)
Warm Up	5 min
Cutting	Flying Knife
Lamination +	SLEEKpro™
Pneumatic	Includes on-board quiet compressor (or house air)
Cooling	Included: Liquid Chiller System for emboss roller
Electrical	Cheetah Photo Laminator: 220-240V 15A Single phase, NEMA 6-15R Chiller System: 110-120V 20A, NEMA 5-20R
Unit Size & Weight	70" L x 30" W x 56" H, 610lbs (Cheetah Photo only)
Crate Size & Weight	52" L x 45" W x 66" H, 880lbs (includes: Laminator/Compressor/Chiller)
Optional Accessories	Automatic Air Pile Feeder

Skandacor[™] is pleased to offer legendary equipment that works brilliantly with our lineup of TRADEpro[™], PHOTOpro[™] and SPECIALTYpro[™] laminate films, as well as digital SLEEKpro[™] foils and finishes.



Note: The information given within this spec sheet is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. SkandacorTM makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The included data is purely for reader's consideration, investigation and verification.

Skandacor™ The **pro**active finish.™

1.888.820.9020 skandacor.com