



Laminating and
Finishing **SYSTEMS**

LAMpro Cheetah S15 Photo

On-Demand, Professional, Compact Specialty Finishing
Laminator & Photo Finisher with Flying Knife



LAMpro Cheetah S15 Photo

The **Cheetah Photo** allows digital printers to replace the traditional silver halide process with simple embossed lamination. This chemical-free process works by combining special laminate film technology with a high-quality digital print to create photos that retain the look, feel, and weight of traditional Silver Halide photos. But unlike the traditional process, the **Cheetah Photo** is more environmentally friendly — it uses no harmful chemicals — and can lower costs by up to 40%.

Finishing Applications in Digital Print Shops, Photo Studios



Specifications



Min. 7" x 8.25"
Max. 15" x 48"



Touch Screen
& Speed Control



220-240V



6-15R

LAMpro Cheetah S15 Photo	
Film Thickness	1.0 mil - 2.0 mil
Max Roll Diameter	14.25"
Core Size	3"
Sheet Size*	Min: 7" x 8.25" Max: 15" x 22" Optional Table extension accepts up to 48"L sheet
Paper Weight*	Min: 120 gsm paper stock Max: 400gsm paper stock (*depending on application)
Optional Feeder	Sheet Size: Min 7" x 9.75" Max 15" x 30" Pile Height 9"
Speed	Simplex lamination: 39 ft/min (1560 12x18 shts/hr) SLEEKpro: 16 ft/min (640 12x18 shts/hr) (depending on application) PHOTOpro Emboss Lamination: 20 ft/min (800 12 x 18 shts/hr)
Warm Up	5 min
Cutting	Flying Knife
Lamination +	SLEEKpro™
Pneumatic	Includes on-board quiet compressor (or house air)
Cooling	Included: Liquid Chiller System for emboss roller
Electrical	Cheetah Photo Laminator: 220-240V 15A Single phase, NEMA 6-15R Chiller System: 220-240V 15A, NEMA 6-15R
Unit Size & Weight	70" L x 30" W x 56" H, 610lbs (Cheetah Photo only)
Crate Size & Weight	52" L x 45" W x 66" H, 880lbs (includes: Laminator/Compressor/Chiller)
Optional Accessories	Automatic Air Pile Feeder

Options Available

LAMpro Systems machines come with modular options that further enhance productivity.



proLINE F15 Feeder
Quoted upon request



Table Jogger
Quoted upon request

Note: The information given within this spec sheet is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Skandacor™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The included data is purely for reader's consideration, investigation and verification.