



Laminating and
Finishing **SYSTEMS**

LAMpro Jaguar D22A

Heavy-Duty, High Speed, Hot Roll Laminator



LAMpro Jaguar D22A

The **LAMpro Jaguar D22A** is a versatile duplex hot roll laminator perfect for both high-volume and short-run lamination tasks. This easy-to-operate laminator features a detachable feeder with a side-lay registration table, which allows you to switch effortlessly between automatic and semi-automatic feeding — according to your job's needs. Film is easily loaded from the operator side of the machine, allowing easy access to the mandrels. Each mandrel is also equipped with air shafts for quick film change-overs. The Jaguar features preheat rollers as well as a heated nip roller system, providing increased adhesion to digital prints. It gets up to temperature in 10 minutes or less and can operate at speeds up to 49 feet/minute*. Side slitters trim excess material from the sides of the sheets, with integrated slit /scrap take-up reels, and six banks of cooling fans provide tremendous cooling capability to the laminated web before slitting/cutting. The **LAMpro Jaguar D22A** is the perfect investment for printers and trade finishing shops looking to streamline their double-sided lamination and encapsulation processes without compromising on quality or productivity. Available with or without the feeder.

Finishing Applications Menus, security applications, credit cards, manuals, passes, tickets, etc.



Specifications


Min. 2" x 6"
Max. 20.4" x 29.5"



220-240 V



Up to 49'/min

	LAMpro Jaguar Feeder (Detachable)	LAMpro Jaguar Laminator
Sheet Size	Min: 8.26" x 8.26" 210 mm x 210 mm Max: 20.4" x 29.5" 518 mm x 749 mm	Min: 2" x 6" 51 mm x 152.4 mm Max: 20.4" x 29.5" 518 mm x 749 mm
Speed*	Up to 49'/min 15 m/min (depending on application)	
Stock weight*	120-400 gsm (depending on application)	
Feeder Capacity	15" 381 mm	
Max. Roll Diameter	14.9" 378 mm	
Film Type	PETpro, NYpro, POLYpro films	
Film Core Size	3" 76.2 mm	
Warm Up Time	10 minutes	
Heating	Infrared heater	
Trimming/Sheeter	Auxiliary cutter (Sold Separately)	
Side Slitters	Included	
Unit Size (L x W x H)	44" x 38" x 61" 112 cm x 96.5 cm x 155 cm	83" x 44" x 62" 210 cm x 117 cm x 157 cm
Weight	2,013 lbs 913 kg	
Electrical	220-240 V, 2A, Single Phase	220-240 V, 40A, Single Phase

Skandacor™ is proud to offer legendary equipment that works brilliantly with our lineup of **TRADEpro™** and **SPECIALTYpro™** laminate films.



TRADE
Laminate Films



SPECIALTY
Thermal
Laminate Films

Note: The information given within this spec sheet is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Skandacor™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The included data is purely for reader's consideration, investigation and verification.

 **skandacor™** The proactive finish.™

1.888.820.9020
skandacor.com