



Laminating and
Finishing **SYSTEMS**

FOILER B3 Auto

High-Performance Digital Foiler



FOILER B3 Auto

The **FOILER B3 Auto** specialty finishing system delivers unmatched foiling over digital toner for medium- to large-scale productions. This is made possible by its advanced heating system — oil-heated, highly stable, and exceptionally robust which provides an unprecedented level of consistent quality. Thanks to extensive re-engineering, the FOILER B3 Auto achieves outstanding performance and reliability. It features high-precision temperature sensors, impressive pressure power, and a fully automatic, deep-pile feeding head for seamless operation.

Finishing Applications in Advertising, Packaging, Specialty Finishing and much more.

Specifications



Min 8.6" x 8.6"
Max. 15" x 27.5"



Up to 33 ft/min



220 -240 V
single phase

	Foiler B3 Auto
Speed	33 ft/min* 10 m/min*
Sheet size & paper weight	Min: 8.6" x 8.6" 220 mm x 220 mm Max: 15" x 27.5" 381mm x 698.5 mm, 130 – 350 gsm
Feeder System	Pneumatic feeder with two air suction units. Stack height 7.9" 200.66 mm and 176 lbs 80 kg capacity.
Varnish thickness	11,8" 300 mm
Foiling unit	Automatic self-regulated accuracy pressure system. Up to 101 Newtons / linear mm pressure.
Delivery unit	1 fan battery for cooling foil. 1 fan battery to ease the exit.
Safety and protection	CE standards, emergency stops and safety sensors. Continuous equipment protection monitoring on feeding, pressure and heating systems.
Unit size & Weight (W x L x H)	42.1" x 80.5" x 57.1" 107 cm x 205 cm x 145 cm 882 lbs 400 kg
Electricals	220 - 240 V single phase, 16 A

*Depending on foil, external conditions, type of paper, paper grammages and formats.

Options Available

Bagel Systems come with modular options that work to further enhance productivity. Contact Skandacor™ to learn more on this lineup of equipment and determine which system will work for your specific needs.




Table Jogger

Note: The information given within this spec sheet is believed to be true and accurate and is not intended to violate any statutory condition or right of a third party. Skandacor™ makes no warranty, express or implied, as to the fitness of the products for any specific use or purpose. The included data is purely for reader's consideration, investigation and verification.